

Environmental Protection Agency**§ 63.1261**

(2) An owner or operator must submit a report 60 days before the scheduled implementation date of either of the following:

(i) Any change in the activity covered by the Precompliance report.

(ii) A change in the status of a control device from small to large.

(i) *Reports of startup, shutdown, and malfunction.* For the purposes of this subpart, the startup, shutdown, and malfunction reports shall be submitted on the same schedule as the periodic reports required under paragraph (g) of this section instead of the schedule specified in § 63.10(d)(5)(i). These reports shall include the information specified in § 63.1259(a)(3)(i) through (iii) and shall contain the name, title, and signature of the owner or operator or other responsible official who is certifying its accuracy. Reports are only required if a startup, shutdown, or malfunction occurred during the reporting period. Any time an owner or operator takes an action that is not consistent with the procedures specified in the affected source's startup, shutdown, and malfunction plan, the owner or operator shall submit an immediate startup, shutdown, and malfunction report as specified in § 63.10(d)(4)(ii).

(j) *Reports of LDAR programs.* The owner or operator of any affected source implementing the LDAR program specified in § 63.1255 of this subpart shall implement the reporting requirements in § 63.1255 of this subpart. Copies of all reports shall be retained as records for a period of 5 years, in accordance with the requirements of § 63.10(b)(1).

(k) *Reports of emissions averaging.* The owner or operator of any affected source that chooses to comply with the requirements of § 63.1252(d) shall submit the implementation plan described in § 63.1259(e) 6 months prior to the compliance date of the standard and the following information in the periodic reports:

(1) The records specified in § 63.1259(e) for each process or storage tank included in the emissions average;

(2) All information as specified in paragraph (g) of this section for each process or storage tank included in the emissions average;

(3) Any changes of the processes or storage tanks included in the average.

(4) The calculation of the overall percent reduction efficiency for the reporting period.

(5) Changes to the Implementation Plan which affect the calculation methodology of uncontrolled or controlled emissions or the hazard or risk equivalency determination.

(6) Every second semiannual or fourth quarterly report, as appropriate, shall include the results according to § 63.1259(e)(4) to demonstrate the emissions averaging provisions of §§ 63.1252(d), 63.1257(g) and (h), 63.1258(f), and 63.1259(f) are satisfied.

(l) *Notification of performance test and test plan.* The owner or operator of an affected source shall notify the Administrator of the planned date of a performance test at least 60 days before the test in accordance with § 63.7(b). The owner or operator also must submit the test plan required by § 63.7(c) and the emission profile required by 63.1257(b)(8)(ii) with the notification of the performance test.

(m) *Request for extension of compliance.* An owner or operator may submit to the Administrator a request for an extension of compliance in accordance with § 63.1250(f)(4).

§ 63.1261 Delegation of authority.

(a) In delegating implementation and enforcement authority to a State under § 112(d) of the Clean Air Act, the authorities contained in paragraph (b) of this section shall be retained by the Administrator and not transferred to a State.

(b) The authority conferred in § 63.177; the authority to approve applications for determination of equivalent means of emission limitation; and the authority to approve alternative test methods shall not be delegated to any State.

§ 63.1261

40 CFR Ch. I (7-1-99 Edition)

TABLE 1 TO SUBPART GGG.—GENERAL PROVISIONS APPLICABILITY TO SUBPART GGG

General provisions reference	Summary of requirements	Applies to sub-part GGG	Comments
63.1(a)(1)	General applicability of the General Provisions	Yes	Additional terms defined in § 63.1251; when overlap between sub-parts A and GGG of this part, subpart GGG takes precedence.
63.1(a)(2-7)	Yes	Discusses state programs.
63.1(a)(8)	Yes	Subpart GGG clarifies the applicability in § 63.1250.
63.1(a)(9-4)	Yes	All major affected sources are required to obtain a title V permit.
63.1(b)(1)	Initial applicability determination	Yes	All affected sources are subject to subpart GGG according to the applicability definition of subpart GGG.
63.1(b)(2)	Title V operating permit—see part 70	Yes	Subpart GGG clarifies the applicability of each paragraph of subpart A to sources subject to subpart GGG.
63.1(b)(3)	Record of the applicability determination	Yes	All major affected sources are required to obtain a title V permit.
63.1(c)(1)	Applicability after standards are set	No	Area sources are not subject to subpart GGG.
63.1(c)(2)	Title V permit requirement	Yes
63.1(c)(3)	Reserved Requirements for existing source that obtains an extension of compliance.	Yes	Notification requirements for an area source that increases HAP emissions to major source levels.
63.1(c)(4)	NA
63.1(c)(5)	Yes	Additional terms defined in § 63.1251; when overlap between sub-parts A and GGG of this part occurs, subpart GGG takes precedence.
63.1(d)	[Reserved] Applicability of permit program before a relevant standard has been set.	Yes	Other units used in subpart GGG are defined in that subpart.
63.1(e)	Definitions.	Yes	Except replace the terms "source" and "stationary source" with "affected source".
63.2	Yes
63.3	Units and abbreviations.	Yes
63.4	Prohibited activities.	Yes
63.5(a)	Construction and reconstruction—applicability	Yes
63.5(b)(1)	Upon construction, relevant standards for new sources	Yes
63.5(b)(2)	[Reserved]	NA	Construction/reconstruction approval.
63.5(b)(3)	New construction/reconstruction	Yes
63.5(b)(4)	Construction/reconstruction notification	Yes
63.5(b)(5)	Construction/reconstruction compliance	Yes
63.5(b)(6)	Equipment addition or process change	Yes
63.5(c)	[Reserved]	NA
63.5(d)	Application for approval of construction/reconstruction	Yes	Except for certain provisions identified in 63.1259(a)(5)
63.5(e)	Yes
63.5(f)	Construction/reconstruction approval based on prior State review.	Yes	Except replace "source" with "affected source".

Environmental Protection Agency
§ 63.1261

63.6(a)(1)	Compliance with standards and maintenance requirements	Yes	
63.6(a)(2)	Requirements for area source that increases emissions to become major.	Yes	
63.6(b)(1-2)	Compliance dates for new and reconstructed sources	No	Subpart GGG specifies compliance dates.
63.6(b)(3-6)	Compliance dates for area sources that become major sources	Yes	Subpart GGG specifies NS applicability and compliance dates.
63.6(b)(7)	Compliance dates for new sources resulting from new unaffected area sources becoming subject to standards.	No	Subpart GGG specifies "affected source". Subpart GGG specifies compliance dates.
63.6(c)	Compliance dates for existing sources	Yes	Except replace "source" with "affected source". Subpart GGG specifies compliance dates.
63.6(e)	Operation and maintenance requirements	Yes	Startup, Shutdown, Malfunction Plan requirements specifically include malfunction process, control and monitoring equipment.
63.6(f)-(g)	Compliance with nonopacity and alternative nonopacity emission standards.	Yes	Except that subpart GGG specifies performance test conditions.
63.6(h)	Opacity and visible emission standards	No	Subpart GGG does not contain any opacity or visible emission standards.
63.6(i)	Extension of compliance with emission standards	No	\$63.1250(f)(4) specifies provisions for compliance extensions.
63.6(j)	Exemption from compliance with emission standards	Yes	Subpart GGG specifies required testing and compliance procedures.
63.7(a)(1)	Performance testing requirements	Yes	Subpart GGG specifies required testing and compliance procedures.
63.7(a)(2)(i-X)	Notification of performance test	Yes	Subpart GGG also contains test methods and procedures specific to pharmaceutical sources.
63.7(a)(3)	Notification of delay in conducting a scheduled performance test	Yes	Subpart GGG provides specific CMS requirements.
63.7(b)(1)	Quality assurance program	Yes	See § 63.1258.
63.7(b)(2)	Notification of delay in conducting a scheduled performance test	Yes	See § 63.1258 of subpart GGG provides specific CMS requirements.
63.7(c)	Performance testing facilities.	Yes	Except that the test plan must be submitted with the notification of the performance test.
63.7(d)	Conduct of performance tests.	Yes	Except replace "source" with "affected source".
63.7(e)	Use of alternative test method	Yes	Subpart GGG also contains test methods and procedures specific to pharmaceutical sources.
63.7(f)	Data analysis, recordkeeping, and reporting	Yes	See § 63.1258.
63.7(g)	Waiver of performance tests	Yes	See § 63.1258.
63.7(h)	Monitoring requirements	Yes	See § 63.1258.
63.8(a)	Conduct of monitoring	Yes	See § 63.1258.
63.8(b)(1)	CMS and combined effluents	No	See § 63.1258.
63.8(b)(3)-(c)(3)	CMS requirements	Yes	See § 63.1258.
63.8(c)(4-5)	CMS operation requirements	Yes	See § 63.1258.
63.8(e)(5-8)	CMS calibration and malfunction provisions	Yes	See § 63.1258.
63.8(d)	CMS quality control program	Yes	See § 63.1258.
63.8(e)(1)	Performance evaluations of CMS	Yes	See § 63.1258.
63.8(e)(2)	Notification of performance evaluation	Yes	See § 63.1258.
63.8(e)(3-4)	CMS requirements/alternatives	Yes	See § 63.1258.
63.8(e)(5)(i)	Reporting performance evaluation results	Yes	See § 63.1258.
63.1260(a)	Results of CMS performance evaluation	No	Subpart GGG does not contain any opacity or visible emission standards.
63.8(e)(5)(ii)	Alternative monitoring methods/reduction of monitoring data	Yes	Subpart GGG does not contain any opacity or visible emission standards.
63.8(f)-(g)	Notification requirements—Applicability and general information	Yes	Subpart GGG does not contain any opacity or visible emission standards.
63.9(a)-(d)	Notification of performance test	Yes	Subpart GGG does not contain any opacity or visible emission standards.
63.9(e)	Notification of opacity and visible emissions observations	No	Subpart GGG does not contain any opacity or visible emission standards.
63.9(f)	Additional notification requirements for sources with CMS	Yes	Subpart GGG does not contain any opacity or visible emission standards.
63.9(g)(1)			

§ 63.1261**40 CFR Ch. I (7-1-99 Edition)**

TABLE 1 TO SUBPART GGG.—GENERAL PROVISIONS APPLICABILITY TO SUBPART GGG—Continued

General provisions ref- erence	Summary of requirements	Applies to sub- part GGG	Comments
63.9(g)(2)	Notification of compliance with opacity emission standard	No	Subpart GGG does not contain any opacity or visible emission standards.
63.9(g)(3)	Notification that criterion to continue use of alternative to relative accuracy testing has been exceeded.	Yes	
63.9(h)	Notification of compliance status.	Yes	
63.9(i)	Adjustment to time periods or postmark deadlines for submittal and review of required communications.	Yes	Due 150 days after compliance date.
63.9(j)	Change in information provided	Yes	
63.10(a)	Recordkeeping requirements	Yes	
63.1259,	Records retention	Yes	Subpart GGG specifies recordkeeping requirements.
63.10(b)(1)	Information and documentation to support notifications	No	Applicability requirements are given in § 63.1250.
63.10(b)(2)	Records retention for sources not subject to relevant standard	Yes	
63.10(b)(3)	Other recordkeeping and reporting provisions	Yes	
63.10(c)-(d)(2)	Reporting results of opacity or visible emissions observations	No	Subpart GGG does not include any opacity or visible emission stand- ards.
63.10(d)(3)	Other recordkeeping and reporting provisions	Yes	
63.10(d)(4-5)	Additional CMS reporting requirements	Yes	
63.10(e)	Waiver of recordkeeping or reporting requirements.	Yes	
63.10(f)	Control device requirements for flares	Yes	
63.11	State authority and delegations	Yes	See § 63.1261.
63.12	Addressess of State air pollution control agencies	Yes	
63.13	Incorporations by reference	Yes	
63.14	Availability of information and confidentiality	Yes	
63.15		Yes	

Environmental Protection Agency**§ 63.1261****TABLE 2 TO SUBPART GGG.—PARTIALLY SOLUBLE HAP**

1,1,1-Trichloroethane (methyl chloroform)
1,1,2,2-Tetrachloroethane
1,1,2-Trichloroethane
1,1-Dichloroethylene (vinylidene chloride)
1,2-Dibromoethane
1,2-Dichloroethane (ethylene dichloride)
1,2-Dichloropropane
1,3-Dichloropropene
2,4,5-Trichlorophenol
2-Butanone (mek)
1,4-Dichlorobenzene
2-Nitropropane
4-Methyl-2-pentanone (mibk)
Acetaldehyde
Acrolein
Acrylonitrile
Allyl chloride
Benzene
Benzyl chloride
Biphenyl
Bromoform (tribromomethane)
Bromomethane
Butadiene
Carbon disulfide
Chlorobenzene
Chloroethane (ethyl chloride)
Chloroform
Chloromethane
Chloroprene
Cumene

TABLE 2 TO SUBPART GGG.—PARTIALLY SOLUBLE HAP—Continued

Dichloroethyl ether
Dinitrophenol
Epichlorohydrin
Ethyl acrylate
Ethylbenzene
Ethylene oxide
Hexachlorobenzene
1,2-Dichlorobutadiene
Hexachloroethane
Methyl methacrylate
Methyl-t-butyl ether
Methylene chloride
N,N-dimethylaniline
Propionaldehyde.
Propylene oxide
Styrene
Tetrachloroethylene (perchloroethylene)
Tetrachloromethane (carbon tetrachloride)
Toluene
Trichlorobenzene (1,2,4-)
Trichloroethylene
Triethylamine
Trimethylpentane
Vinyl acetate
Vinyl chloride
Xylene (m)
Xylene (o)
Xylene (p)
N-hexane

TABLE 3 TO SUBPART GGG.—SOLUBLE HAP

Compound
1,1-Dimethylhydrazine.
1,4-Dioxane.
Acetonitrile.
Acetophenone.
Diethyl sulfate.
Dimethyl sulfate.
Dinitrotoluene.
Ethylene glycol dimethyl ether.
Ethylene glycol monobutyl ether acetate.
Ethylene glycol monomethyl ether acetate.
Isophorone.
Methanol (methyl alcohol).
Nitrobenzene.
Toluidene.

§ 63.1261

40 CFR Ch. I (7-1-99 Edition)

TABLE 4 TO SUBPART GGG.—MONITORING REQUIREMENTS FOR CONTROL DEVICES^a

Control device	Monitoring equipment required	Parameters to be monitored	Frequency
All control devices	1. Flow indicator installed at all bypass lines to the atmosphere and equipped with continuous recorder or. 2. Valves sealed closed with car-seal or lock-and-key configuration. Liquid flow rate or pressure drop monitoring device. Also a pH monitor if the scrubber is used to control acid emissions.	1. Presence of flow diverted from the control device to the atmosphere or. 2. Monthly inspections of sealed valves	Hourly records of whether the flow indicator was operating and whether a diversion was detected at any time during each hour. Monthly.
Scrubber	1. Liquid flow rate into or out of the scrubber or the pressure drop across the scrubber. 2. pH of effluent scrubber liquid	1. Every 15 minutes. 2. Once a day. Every 15 minutes.
Thermal incinerator	Temperature monitoring device installed in firebox or in ductwork immediately downstream of firebox.	Firebox temperature	Every 15 minutes.
Catalytic incinerator	Temperature monitoring device installed in gas stream immediately before and after catalyst bed.	Temperature difference across catalyst bed ..	Every 15 minutes.
Flare	Heat sensing device installed at the pilot light stream of firebox ^b .	Presence of a flame at the pilot light	Every 15 minutes.
Boiler or process heater <44 mega watts and vent stream is not mixed with the primary fuel.	Temperature monitoring device installed in firebox ^b .	Combustion temperature	Every 15 minutes.
Condenser	Temperature monitoring device installed at condenser exit.	Condenser exit (product side) temperature ..	Operating time since last replacement
Carbon adsorber (nonregenerative)	None	1. Total regeneration stream mass or volumetric flow during carbon bed regeneration cycle(s). 2. Temperature of carbon bed after regeneration.	N/A.
Carbon adsorber (regenerative)	Stream flow monitoring device, and	3. Temperature of carbon bed within 15 minutes of completing any cooling cycle(s). 4. Operating time since end of last regeneration.	1. For each regeneration cycle, record the total regeneration stream mass or volumetric flow. 2. For each regeneration cycle, record the maximum carbon bed temperature. 3. Within 15 minutes of completing any cooling cycle, record the carbon bed temperature. 4. Operating time to be based on worst-case conditions. 5. Check for bed poisoning

^aAs an alternative to the monitoring requirements specified in this table, the owner or operator may use a CEM meeting the requirements of Performance Specifications 8 or 9 of appendix B of part 60 to monitor TOC every 15 minutes.

^bMonitor may be installed in the firebox or in the ductwork immediately downstream of the firebox before any substantial heat exchange is encountered.

Environmental Protection Agency
§ 63.1261

TABLE 5 TO SUBPART GGG.—CONTROL REQUIREMENTS FOR ITEMS OF EQUIPMENT THAT MEET THE CRITERIA OF § 63.1252(F)

Item of equipment	Control requirement ^a
Drain or drain hub	(a) Tightly fitting solid cover (TFSC); or (b) TFSC with a vent to either a process, or to a fuel gas system, or to a control device meeting the requirements of § 63.1256(h)(2); or (c) Water seal with submerged discharge or barrier to protect discharge from wind.
Manhole ^b	(a) TFSC; or (b) TFSC with a vent to either a process, or to a fuel gas system, or to a control device meeting the requirements of § 63.1256(h)(2); or (c) If the item is vented to the atmosphere, use a TFSC with a properly operating water seal at the entrance or exit to the item to restrict ventilation in the collection system. The vent pipe shall be at least 90 cm in length and not exceeding 10.2 cm in nominal inside diameter.
Lift station	(a) TFSC; or (b) TFSC with a vent to either a process, or to a fuel gas system, or to a control device meeting the requirements of § 63.1256(h)(2); or (c) If the lift station is vented to the atmosphere, use a TFSC with a properly operating water seal at the entrance or exit to the item to restrict ventilation in the collection system. The vent pipe shall be at least 90 cm in length and not exceeding 10.2 cm in nominal inside diameter. The lift station shall be level controlled to minimize changes in the liquid level.
Trench	(a) TFSC; or (b) TFSC with a vent to either a process, or to a fuel gas system, or to a control device meeting the requirements of § 63.1256(h)(2); or (c) If the item is vented to the atmosphere, use a TFSC with a properly operating water seal at the entrance or exit to the item to restrict ventilation in the collection system. The vent pipe shall be at least 90 cm in length and not exceeding 10.2 cm in nominal inside diameter.
Pipe	Each pipe shall have no visible gaps in joints, seals, or other emission interfaces
Oil/Water separator	(a) Equip with a fixed roof and route vapors to a process or to a fuel gas system, or equip with a closed-vent system that routes vapors to a control device meeting the requirements of § 63.1256(h)(2); or (b) Equip with a floating roof that meets the equipment specifications of § 60.693 (a)(1)(i), (a)(1)(ii), (a)(2), (a)(3), and (a)(4).
Tank	Maintain a fixed roof. ^c If the tank is sparged ^d or used for heating or treating by means of an exothermic reaction, a fixed roof and a system shall be maintained that routes the organic hazardous air pollutants vapors to other process equipment or a fuel gas system, or a closed-vent system that routes vapors to a control device that meets the requirements of 40 CFR § 63.119 (e)(1) or (e)(2).

^a AAA^a Where a tightly fitting solid cover is required, it shall be maintained with no visible gaps or openings, except during periods of sampling, inspection, or maintenance.

^b AAA^b Manhole includes sumps and other points of access to a conveyance system.

^c AAA^c A fixed roof may have openings necessary for proper venting of the tank, such as pressure/vacuum vent, j-pipe vent.

^d AAA^d The liquid in the tank is agitated by injecting compressed air or gas.

TABLE 6 TO SUBPART GGG.—WASTEWATER—COMPLIANCE OPTIONS FOR WASTEWASTER TANKS

Capacity, m ³	Maximum true vapor pressure, kPa	Control requirements
<75	§ 63.1256(b)(1).
>75 and <151	<13.1 >13.1	§ 63.1256(b)(1). § 63.1256(b)(2).
>151	<5.2 >5.2	§ 63.1256(b)(1). § 63.1256(b)(2).

§ 63.1261

40 CFR Ch. I (7-1-99 Edition)

TABLE 7 TO SUBPART GGG.—WASTEWATER—INSPECTION AND MONITORING REQUIREMENTS FOR WASTE MANAGEMENT UNITS

To comply with	Inspection or monitoring requirement	Frequency of inspection or monitoring	Method
TANKS:			
63.1256(b)(3)(i)	Inspect fixed roof and all openings for leaks.	Initially Semiannually	Visual.
63.1256(b)(4)	Inspect floating roof in accordance with §§ 63.120(a)(2) and (a)(3).	See §§ 63.120(a)(2) and (a)(3)	Visual.
63.1256(b)(5)	Measure floating roof seal gaps in accordance with §§ 63.120(b)(2)(i) through (b)(4).	See § 63.120(b)(2)(i) through (b)(4).
63.1256(b)(7)	—Primary seal gaps	Initially Once every 5 years (annually if no secondary seal).	Visual.
63.1256(b)(8)	—Secondary seal gaps	Initially Semiannually	Visual.
SURFACE IMPOUNDMENTS:			
63.1256(c)(1)(i)	Inspect cover and all openings for leaks	Initially Semiannually	Visual.
63.1256(c)(2)	Inspect surface impoundment for control equipment failures and improper work practices.	Initially Semiannually	Visual.
CONTAINERS:			
63.1256(d)(1)(i)	Inspect cover and all openings for leaks	Initially Semiannually	Visual.
63.1256(d)(1)(ii)	Inspect endosure and all openings for leaks.	Initially Semiannually	Visual.
63.1256(d)(3)(i)	Inspect container for control equipment failures and improper work practices.	Initially Semiannually	Visual.
INDIVIDUAL DRAIN SYSTEMS*:			
63.1256(e)(1)(i)	Inspect cover and all openings to ensure there are no gaps, cracks, or holes.	Initially Semiannually	Visual.
63.1256(e)(2)	Inspect individual drain system for control equipment failures and improper work practices.	Initially Semiannually	Visual.
63.1256(e)(4)(i)	Verify that sufficient water is present to properly maintain integrity of water seals.	Initially Semiannually	Visual.
63.1256(e)(4)(ii)	Inspect all drains using tightly-fitted caps or plugs to ensure caps and plugs are in place and properly installed.	Initially Semiannually	Visual.
63.1256(e)(5)(i)	Inspect all junction boxes to ensure covers are in place and have no visible gaps, cracks, or holes.	Initially Semiannually	Visual or smoke test or other means as specified.
OIL-WATER SEPARATORS:			
63.1256(e)(5)(iii)	Inspect unburied portion of all sewer lines for cracks and gaps.	Initially Semiannually	Visual.

63.1256(f)(2)(i)	Inspect fixed roof and all openings for leaks.	Initially Semianually	Visual.
63.1256(f)(3)	Measure floating roof seal gaps in accordance with 40 CFR 60.696(d)(1).	Initially ^b	See 40 CFR 60.696(d)(1).
	—Primary seal gaps	Once every 5 years.	
	—Secondary seal gaps	Initially ^b Annually.	
63.1256(f)(3)	Inspect oil-water separator for control equipment failures and improper work practices.	Initially Semianually	Visual.
63.1256(f)(4)			

^a As specified in § 63.1256(e), the owner or operator shall comply with either the requirements of § 63.1256(e)(1) and (2) or § 63.1256(e)(4) and (5).

^b Within 60 days of installation as specified in § 63.1256(f)(3).

§ 63.1261

40 CFR Ch. I (7-1-99 Edition)

TABLE 8 TO SUBPART GGG.—FRACTION MEASURED (F_m) FOR HAP COMPOUNDS IN WASTEWATER STREAMS

Chemical name	CAS No. ^a	F_m
Acetaldehyde	75070	1.00
Acetonitrile	75058	0.99
Acetophenone	98862	0.31
Acrolein	107028	1.00
Acrylonitrile	107131	1.00
Allyl chloride	107051	1.00
Benzene	71432	1.00
Benzyl chloride	100447	1.00
Biphenyl	92524	0.86
Bromoform	75252	1.00
Butadiene (1,3-)	106990	1.00
Carbon disulfide	75150	1.00
Carbon tetrachloride	56235	1.00
Chlorobenzene	108907	0.96
Chloroform	67663	1.00
Chloroprene (2-Chloro-1,3-butadiene)	126998	1.00
Cumene	98828	1.00
Dichlorobenzene (p-1,4-)	106467	1.00
Dichloroethane (1,2-) (Ethylene dichloride)	107062	1.00
Dichloroethylene (Bis(2-Chloroethyl ether))	111444	0.76
Dichloropropene (1,3-)	542756	1.00
Diethyl sulfate	64675	0.0025
Dimethyl sulfate	77781	0.086
Dimethylaniline (N,N-)	121697	0.00080
Dimethylhydrazine (1,1-)	57147	0.38
Dinitrophenol (2,4-)	51285	0.0077
Dinitrotoluene (2,4-)	121142	0.085
Dioxane (1,4-) (1,4-Diethyleneoxide)	123911	0.87
Epichlorohydrin(1-Chloro-2,3-epoxypropane)	106898	0.94
Ethyl acrylate	140885	1.00
Ethylbenzene	100414	1.00
Ethyl chloride (Chloroethane)	75003	1.00
Ethylene dibromide (Dibromomethane)	106934	1.00
Ethylene glycol dimethyl ether	110714	0.86
Ethylene glycol monobutyl ether acetate	112072	0.043
Ethylene glycol monomethyl ether acetate	110496	0.093
Ethylene oxide	75218	1.00
Ethyldiene dichloride (1,1-Dichloroethane)	75343	1.00
Hexachlorobenzene	118741	0.97
Hexachlorobutadiene	87683	0.88
Hexachloroethane	67721	0.50
Hexane	110543	1.00
Isophorone	78591	0.47
Methanol	67561	0.85
Methyl bromide (Bromomethane)	74839	1.00
Methyl chloride (Chloromethane)	74873	1.00
Methyl ethyl ketone (2-Butanone)	78933	0.99
Methyl isobutyl ketone (Hexone)	108101	0.98
Methyl methacrylate	80626	1.00
Methyl tert-butyl ether	1634044	1.00
Methylene chloride (Dichloromethane)	75092	1.00
Naphthalene	91203	0.99
Nitrobenzene	98953	0.39
Nitropropane (2-)	79469	0.99
Phosgene	75445	1.00
Propionaldehyde	123386	1.00
Propylene dichloride (1,2-Dichloropropane)	78875	1.00
Propylene oxide	75569	1.00
Styrene	100425	1.00
Tetrachloroethane (1,1,2,2-)	79345	1.00
Tetrachloroethylene (Perchloroethylene)	127184	1.00
Toluene	108883	1.00
Toluidine (o-)	95534	0.15
Trichlorobenzene (1,2,4-)	120821	1.00
Trichloroethane (1,1,1-) (Methyl chloroform)	71556	1.00
Trichloroethane (1,1,2-) (Vinyl Trichloride)	79005	0.98
Trichloroethylene	79016	1.00
Trichlorophenol (2,4,5-)	95954	1.00
Triethylamine	121448	1.00
Trimethylpentane (2,2,4-)	540841	1.00
Vinyl acetate	108054	1.00

Environmental Protection Agency**§ 63.1270**TABLE 8 TO SUBPART GGG.—FRACTION MEASURED (F_m) FOR HAP COMPOUNDS IN WASTEWATER STREAMS—Continued

Chemical name	CAS No. ^a	F_m
Vinyl chloride (Chloroethylene)	75014	1.00
Vinyldene chloride (1,1-Dichloroethylene)	75354	1.00
Xylene (m-)	108383	1.00
Xylene (o-)	95476	1.00
Xylene (p-)	106423	1.00

^aCAS numbers refer to the Chemical Abstracts Service registry number assigned to specific compounds, isomers, or mixtures of compounds.

TABLE 9 TO SUBPART GGG.—DEFAULT BIORATES FOR LIST 1 COMPOUNDS

Compound name	Biorate (K1), L/g MLVSS-hr
Acetonitrile	0.100
Acetophenone	0.538
Diethyl sulfate	0.105
Dimethyl hydrazine(1,1)	0.227
Dimethyl sulfate	0.178
Dinitrotoluene(2,4)	0.784
Dioxane(1,4)	0.393
Ethylene glycol dimethyl ether	0.364
Ethylene glycol monomethyl ether acetate	0.159
Ethylene glycol monobutyl ether acetate	0.496
Isophorone	0.598
Methanol	(^a)
Nitrobenzene	2.300
Toluidine (-O)	0.859

^aFor direct dischargers, the default biorate for methanol is 3.5 L/g MLVSS-hr; for indirect dischargers, the default biorate for methanol is 0.2 L/g MLVSS-hr.

Subpart HHH—National Emission Standards for Hazardous Air Pollutants From Natural Gas Transmission and Storage Facilities

SOURCE: 64 FR 32648, June 17, 1999, unless otherwise noted.

§ 63.1270 Applicability and designation of affected source.

(a) This subpart applies to owners and operators of natural gas transmission and storage facilities that transport or store natural gas prior to entering the pipeline to a local distribution company or to a final end user (if there is no local distribution company), and that are major sources of hazardous air pollutants (HAP) emissions as determined using the maximum natural gas throughput calculated in either paragraph (a)(1) or (a)(2) of this section and paragraphs (a)(3) and (a)(4) of this section. A compressor station that transports natural gas prior to the point of custody transfer, or to a natural gas processing plant (if present) is considered a part of the

oil and natural gas production source category. A facility that is determined to be an area source, based on emission estimates using the maximum natural gas throughput calculated as specified in paragraph (a)(1) or (a)(2) of this section, but subsequently increases emissions or potential to emit above the major source levels (without first obtaining and complying with other limitations that keep its potential to emit HAP below major source levels), becomes a major source and must comply thereafter with all applicable provisions of this subpart starting on the applicable compliance date specified in paragraph (d) of this section. Nothing in this paragraph is intended to preclude a source from limiting its potential to emit through other appropriate mechanisms that may be available through the permitting authority.

(1) Facilities that store natural gas or facilities that transport and store natural gas shall determine major source status using the maximum annual facility natural gas throughput calculated according to paragraphs